



Features

- Compact and easy- to-use
- Excellent, optimized audio characteristics
- One-button operation
- Wireless noise transmission
- Built-in LED light
- Wireless range of 66 ft
- 3 fixed filter settings
- Mute setting (no hissing in the headphones)
- Immediate detection of leaks

Standard Equipment

- HL 5 with FM transmitter using 900 MHz technology
- Wireless headphone with FM receiver
- 2 AA batteries for the HL 5 unit
- 3 AAA batteries for the headphones
- Extension rod and magnet
- Hard Case
- Operating Manual

Description

The HL 5 is a professional and flexible mini water leak detection unit with both a visual and audible indication of a leak and the wireless transmission of the leak noise.

Wireless transmission of the leak sound to the headphones provides maximum freedom of movement. The extremely sensitive piezo-ceramic sensors have an automatic level control that enables excellent quality analysis even on plastic piping.

The built-in light is great for improving visibility in low light areas.



Service Center, Sales and Technical Support Information

Corporate Headquarters
3251 Olcott Street
Santa Clara, CA 95054
800-638-7682
408-734-1400 Direct
408-734-1415 Fax
www.metrotech.com
sales@metrotech.com

Metrotech Eastern U.S. Service Center
1824 Murfreesboro Road, Ste. 104
Nashville, TN 37217
800-624-6210
615-366-7323 Direct
615-360-9855 Fax
nashville@metrotech.com

Metrotech European Service Center
SebaKMT
Dr.-Herbert-Iann-Str. 6
D-96148 Baunach, Germany
+49-9544-680 Direct
+49-9544-2273 Fax
www.sebakmt.com
service@sebakmt.com

Metrotech HL 5™

Leak Status	LED display
Resolution	0-10 noise levels
HL 5 Batteries	2 AA batteries
Headphone Batteries	3 AAA batteries
Filter	3 fixed filter settings (low, broadband, high)
Frequency range	40 to 4000 Hz
Transmission range	Up to 66 ft
Light	LED light, integrated
Radio frequency	900 MHz
Dimensions	11.4cm x 3.5cm x 2.5 cm
Wireless Range	Approx. 66 ft.
Battery	Approximately 50 hours

Specifications are subject to change without notice. Not all options and features may be listed here, contact Metrotech for details on specific instrument features and options.



Service Center, Sales and Technical Support Information

Corporate Headquarters
3251 Olcott Street
Santa Clara, CA 95054
800-638-7682
408-734-1400 Direct
408-734-1415 Fax
www.metrotech.com
sales@metrotech.com

Metrotech Eastern U.S. Service Center
1824 Murfreesboro Road, Ste. 104
Nashville, TN 37217
800-624-6210
615-366-7323 Direct
615-360-9855 Fax
nashville@metrotech.com

Metrotech European Service Center
SebaKMT
Dr.-Herbert-Iann-Str. 6
D-96148 Baunach, Germany
+49-9544-680 Direct
+49-9544-2273 Fax
www.sebakmt.com
service@sebakmt.com